

Encoder Series

HP801P MPEG-4 AVC/H.264 HD Encoder



Outline

HP801P Single MPEG4 AVC/H.264 HD Encoder is the new broadcasting audio and video encoding device. It adopts the most advanced AVC/H.264 audio encoding algorithm, and combines with our company's advanced audio and video pre-dealing technology. This device can encode and transmit high-quality audio & video under the low bit-rate. Also, it has several analog and digital video input interfaces (CVBS, YPbPr, SDI, and HDMI), and audio input interfaces (RCA, XLR, HDMI, AES and EBU). Its high integrate and cost effective design gives users excellent digital video encoding solution, and makes it widely used in DMB-T international modulator group net, Terrestrial digital TV and image monitoring etc.

Features

- AVC/H.264 High Profile Level 4.0 high profile level video encoding, advanced video pretreatment technology
- MPEG-1 Audio Layer2 audio encoding (HE_AAC(v2) and LC-AAC audio encoding are optional, as per customer's order)

Encoder Series

HP801P MPEG-4 AVC/H.264 HD Encoder

- UDP/RTP media transmission protocols & unicast/multicast output support
- CVBS,S-VIDEO and YPbPr analog video input interfaces
- HDMI and SDI digital video input
- XLR, RCA analog audio input
- AES/EBU digital audio input
- PAL and NTSC SD video formats
- 720P and 1080I HD video formats
- LCD/keyboard control method
- NMS for remote control

Specifications

Video input		1 × Analog CVBS, BNC interface 1 ×S-Video input, BNC interface 1 × YPbPr video input, BNC interface HD/SD-SDI, BNC interface HDMI interface
Audio input		Analog stereo audio(balanced), XLR interface Analog stereo audio(unbalanced), BNC interface AES / EBU digital audio, XLR interface HD/SD-SDI embedded audio
Video	Resolution	1920x1080_59.94p, 1920x1080_50p 1920×1080_59.94i, 1920×1080_50i, 1280×720_59.94p, 1280×720_50p 720×480_59.94i(NTSC), 720×576_50i(PAL)
		AVC/H.264 High Profile Level 4.0 for HD AVC/H.264 High Profile Level 3.0 for SD
		0.8Mbps~20Mbps
		CBR/VBR
	GOP Structure	IBBP
	Advanced Pretreatment	De-interlacing, noise reduction, sharpening

Encoder Series

HP801P MPEG-4 AVC/H.264 HD Encoder

Audio	Encoding	MPEG-1 Layer 2 (HE_AAC(v2) and LC-AAC audio encoding are optional, as per customer's order)
	Sampling rate	48KHz
	Bit-rate	32Kb/s~384Kb/s
Stream output		2×ASI outputs, BNC interface SPTS over UDP/RTP, 10/100Base-T Ethernet interface (UDP/RTP unicast / multicast)
System function		LCD/keyboard operating, NMS support Chinese-English control interface Ethernet software upgrade
General	Dimensions	482mm×455mm×44.5mm (W × D × H)
	Approx weight	8Kg
	Temperature range	0~45°C(Operation), -20~80°C(Storage)
	Power requirement	AC110V±10%, 50/60Hz; AC 220V±10%,50/60Hz
	Power Consumption	17.6W

Principle Chart

