

Cat  *Cast*



HPR1901E
ENCODER MODULATOR

INTRODUCTION

HPR1901E encoder modulator is the most cost-effective and smallest form factor solution in the market. With the second HDMI output port and a RF loop port, user can easily install the system with different requirements. Extremely compact and wall mountable, It fits into any space virtually.

FEATURES

- 1 channels HDMI input
- Extremely compact with less than 3CM height
- Support MPEG-2 encoding
- MER greater than 35dB
- Integrated HDMI output for HD content quick display
- High output level with 45dBmV MAX
- Built-in Web UI allow for easy set-up and control visa the web browser

SPECIFICATION

ENCODING			
Input Connector	HDMI 1.4		
VIDEO	Encoding	MPEG-2	
	Input Resolution	1920*1080_60P; 1920*1080_50P; 1920*1080_60i; 1920*1080_50i; 1280*720_60P; 1280*720_50P	
	Bitrate	2 ~ 18 Mbps	
AUDIO	Encoding	MPEG 1 Layer II	
	Sample Rate	48KHz	
	Bitrate	384kbps	
MODULATION			
ATSC	Standard	ATSC A/53 (6M)	
	Constellation	8VSB	
	MER	≥ 32 dB	
DVB-C J.83B	Standard	Annex B (6M)	
	Constellation	64QAM, 256QAM	
	MER	≥ 36 dB	
OUTPUT			
RF	Output Level	≥ 45 dBmV	
	Output Frequency Range	50 ~ 999.999MHz	
	Out-band Rejection	≥ 60dB	
LOOP OUTPUT			
HDMI OUT	HDMI 1.4	RF LOOP	F Connector
SYSTEM			
Management	Control Keys; NMS;	LCN Insertion	YES
Language	English	Upgrade	NMS
GENERAL			
Power Supply	DC 12V	Power Consumption	