




# LED

*Cube*

## Cube-165 Lighting Kits assembly & introduction

### Features & Benefits

- \* Mechanical compatibility with direct mounting of the COB products to the LED thermal body and thermal performance matching the lumen packages.
- \* For Down light designs from 3200 to 4500 lumen.
- \* Thermal resistance range Rth 1.21°C/W.
- \* Full accessory kit with LED cooler Body, PSU mounting shrapnel & lens holder.
- \* Other accessories like COB holder & lens separate available.
- \* Modular design with mounting holes foreseen for direct mounting of a wide range of LED modules and COB's.
- \* Forged from highly conductive aluminum (ADC12) .
- \* Dimension 160x160mm - Standard height 165 mm , Other heights on request.
- \* 3 standard colors - white powder,black powder and gray powder.



- 01) Bridelux: Vero 10/13 Vero SE 10/13 LED engines;
- 02) Cree: XLamp CXA 13xx, Xlamp CXB 15xx, CXA 18xx Series engines;
- 03) Citizen: CLU026,CLU027,CLU028,CLU036,CLU038,CLU721,CLU711, CLU701 LED engines;
- 04) Edison: EdiLex III COB LED engines;
- 05) GE lighting: Infusion™ LED engines;
- 06) LG Innotek: 7W, 10W, 16W, 21W, 32W LED engines;
- 07) Lumileds: LUXEON 1202/1203/1204/1205/1208 LED engines;
- 08) Lumens: Ergon-COB 15xx, 18xx LED engines;
- 09) Luminus: CXM-6, CHM/CLM/CXM-9/14/18 LED engines;
- 10) Nichia: NVxxx024Z,NVxxx036Z, NFCWxxxB Series LED engines;
- 11) Osram: SOLERIQ® S 9/S13, Z6 Mini LED engines;
- 12) Philips: Fortimo SLM LED engines;
- 13) Prolight Opto: PACJ-7xxx/14xxx/21xxx/28xxx-xxxx, PACK-35xxx/42xxx/57xxx-xxxx engines;
- 14) Samsung: LCxxxC Series, LCxxxD Series LED engines;
- 15) Seoul Semiconductor:SAWxxxxxx Series, DC COB LED engines;
- 16) Tridonic: SLE G5, SLE G6 10/15/17mm LED engines;
- 17) Vossloh-Schwabe: LUGA Shop and LUGA C LED engines;

### Order Information



Example: Cube-165-WH

- Cube - **1** - **2**
- 1** Product model  
- 165
  - 2** Finish  
- WH White  
- BK Black  
- GY Gray

Notes:  
 - Mentioned models are an extraction of full product range.  
 - For specific mechanical adaptations please contact MingfaTech.  
 - MingfaTech reserves the right to change products or specifications without prior notice.



**The product data table**

	 <i>Cube</i>
<b>Model No.</b>	<b>Cube-165</b>
<b>Heatsink Size</b>	<b>160x160x165 mm</b>
<b>Heatsink Material</b>	<b>ADC12</b>
<b>Heatsink Finish</b>	<b>White/Black/Gray</b>
<b>Weight</b>	<b>1755g</b>
<b>Dissipated power (Ths-amb,50°C)</b>	<b>40 (W)</b>
<b>Beam Angle</b>	<b>50°</b>
<b>Thermal Resistance (Rhs-amb)</b>	<b>1.21(°C/W)</b>

\* 3D files are available in ParaSolid, STP and IGS on request

\* The thermal resistance Rth is determined with a calibrated heat source of 18mmx18mm central placed on the heat sink, Tamb 40° and an open environment. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C  
 The thermal resistance of a LED cooler is not a fix value and will vary with the applied dissipated power Pd

\* Dissipated power Pd. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C  
 The maximal dissipated power needs to be verified in function of required case temperature Tc or junction temperature Tj and related to the estimated ambient temperature where the light fixture will be placed  
 Please be aware the dissipated power Pd is not the same as the electrical power Pe of a LED module

To calculate the dissipated power please use the following formula:  $Pd = Pe \times (1-\eta L)$   
 Pd - Dissipated power  
 Pe - Electrical power  
 $\eta L$  = Light efficiency of the LED module