Shenzhen SMX Display Technology Co.,Ltd

www.smxdisplay.com

Address: 611, Block A, Zhihui Innovation Center, Xixiang St., Baoan Dist., Shenzhen,China

Contact: May Wei Email: may@smxdisplay.com Whatsapp/ Wechat: 0086 18923801593

7000 Lumen Short Throw 3LCD Laser Projector WUXGA		
Key Parts		
	Model No.	MX-SL750U
	Brightness(Lumen)	**7500**
	ID. Photo	
Overall Spec		
Panel	Display Panel	3x0.64" with MLA
	Light source	NICHIA LASER
	Display Technology	Liquid Crystal Display
	Native Resolution	WUXGA (1920 x 1200)
Light source Life time	Full Normal/Normal mode	20000hrs
	ECO1 mode	30000hrs
	ECO2 mode	30000hrs
Projection Lens	F	1.7~1.8
	f	9.66mm-11.65mm
	Zoom/Focus	Manual
	Throw Ratio	0.68 (wide)-0.82 (tele)
	Zoom Ratio	1.21
	Screen size	50-300inch
	Lens Shift	V:＋50%～0%、 H:±20%
CR	Contrast Ratio	5,000,000:1
Noise	Noise(dB)	39dB(Normal) 31dB(ECO1)/29dB(ECO2)
Uniformity	Uniformity	80%
AR	Aspect Ratio	Native:16:10 Compatible: 4:3/16:9
Terminal(I/O port)		
Input	VGA	*1
	HDMI 1.4B(IN)	*2
	USB-A	*1
	USB-B	*1 (Display)
	RJ45	*1(Display)
	HD BaseT	*1(Optional)
	Audio in (mini jack,3.5mm)	*1
Output	VGA	*1
	Audio out (mini-jack,3.5mm)	*1
Control	RS232	*1
	RJ45	*1 (Control)
	USB-B	*1 (For upgrade)

General Spec		
Audio	Speaker	16W*1
Dust filter		W/Filter
Filter Life time		8000h
Power Consumption	Power Requeirements	100~240V@ 50/60Hz
	ECO Standby Mode Power Consumption	<0.5W
Temp.&Humidity	Operating Temp.	0m≤Altitude≤1700m, Ambient0℃~50℃
		1700m＜Altitude＜3000m, Ambient 0℃~40℃
	Operating humidity.	20-85%
	Store Temp.	-10 to 50°C
	High altitude	0~3000m
Other Functions		
Keystone	Keystone Correction (Lens@center)	V: ±15° H: ±15° Pincushion/Barrel Correction 6 Corner Geometry correction 4 Corner Correction Grid image tune
OSD	Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak,Vietnamese,Thai, Farsi
LAN Control	LAN Control-RoomView (Crestron)	Yes
	LAN Control--AMX Discovery	Yes
	LAN Control-- PJ Link	Yes
Scanning Frequency	H-Synch Range	15~100KHz
	V-Synch Range	24~85Hz
Display Resolution	Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,4K@30Hz
	Video Signal Input	480i, 480p, 576i, 576p, 720p, 1080i and 1080p
SW Setting	Auto Setup	INPUT SEARCH,AUTO PC,Auto Keystone
	Blank	Yes
	Suspend	Yes(5 minutes no signal as default)
	Picture mode	Dynamic，Standard，Cinema， Colorboard，sim-DICOM,Blackboard(Green)
	Cooling time	0s、normal、30s
	Auto Ceiling	Yes
	D-Zoom	1~33
Others	360° projection	Yes
	Edge Blending	Yes
Dimension&Weight		
	Product Size (mm)	405(W)×404(D)×164(H)
	Net. Weight (KG)	8.1kg
	Packaging Size(mm)	510(W)×498(D)×260(H)
	Gross. Weight (KG)	~10.4KG
Accessory		
	Manual Languages	Chinese,English
	Standard Accessaries	Power cord, HDMI cable, Remote control