

**Product Characteristics**

**Centrifuge FLC-04C**



- Strong Plastic case with metal lid
- High Brushless motor, LED display speed and time
- Over speed and imbalance alarm
- With mechanical door lock and safety switch
- Error code display, speed up and down adjustment
- Suit for qualitative analysis of blood serum and plasma in hospitals and biochemical laboratories.

Model	FLC-04C
MAX RPM	4000 RPM, stepless speed adjustment , LED display speed and time
Max RCF	2325xg
Time	0-99min
Rotor capacity	20mlx12 (standard)
Voltage	110V 60Hz /220V50Hz
Dimension(mm)	280x310x265
Weight	9kg

Model	Ordering number	Rotor capacity	Max RCF
<b>FLC-04C</b>	A042012 (standard)	20mlx12	2325xg
Centrifuge FLC-04C with	A042006	20mlx6	1790xg
Centrifuge FLC-04C with	A042008	20mlx8	2325xg
Centrifuge FLC-04C with	A041518	15mlx18	2325xg
Centrifuge FLC-04C with	A041012	10mlx12	2325xg
Centrifuge FLC-04C with	A040512	5ml eppendorf tube x12	1790xg

**Product Characteristics**

**Centrifuge FLC-04L**



- Strong Plastic case
- Brushless motor, LCD display speed, RCF and time
- Over speed and imbalance alarm
- Touch panel control, automatic stop once lid open
- Error code display, speed up and down adjustment
- Suit for qualitative analysis of blood serum and plasma in hospitals and biochemical laboratories.

Model	FLC-04L
MAX RPM	4000 RPM, stepless speed adjustment , LCD display speed ,RCF and time
Max RCF	2325xg
Time	0-99min
Rotor capacity	20mlx12 (standard)
Voltage	110V 60Hz /220V50Hz
Dimension(mm)	320x340x280
Weight	9kg

Model	Ordering number	Rotor capacity	Max RCF
<b>FLC-04L</b>	A042012 (standard)	20mlx12	2325xg
Centrifuge FLC-04L with	A042008	20mlx8	2325xg
Centrifuge FLC-04L with	A041518	15mlx18	2325xg
Centrifuge FLC-04L with	A040512	5ml eppendorf tube x12	1790xg

**Product Characteristics**

**PRP Centrifuge FLC-04P**



- Strong Plastic case with microprocessor control
- DC Brushless motor, LED display speed and time
- Over speed and imbalance alarm
- With mechanical door lock
- Error code display, speed up and down adjustment
- Used for PRP/PPP
- Suit for centrifuge the 10 ml syringe directly
- It is dedicated product for the beauty salon

Model	FLC-04P
MAX RPM	4000 RPM, stepless speed adjustment , LED display speed and time
Max RCF	1780xg
Time	0-99min
Rotor capacity	Angle rotor 15ml /10mlx8
Voltage	110V 60Hz /220V 50Hz
Dimension(mm)	280x250x240
Weight	7kg

**Product Characteristics**

**On-board Centrifuge FLC-04M**



- Strong Plastic case with microprocessor control
- DC Brushless motor,
- LED display speed and time
- Tri-temp Motor, extend motor's life
- Power input 12V, accept for vechile using
- With mechanical door lock
- Error code display, speed up and down adjustment

Model	FLC-04M
MAX RPM	4000 RPM, stepless speed adjustment , LED display speed and time
Max RCF	2325xg
Time	0-99min
Rotor capacity	Angle rotor 20mlx12
Voltage	12V
Dimension(mm)	280x310x265
Weight	9kg