

FHM-3000A Series Bacti-Cinerator Sterilizer

Features

The Bacti-Cinerator Sterilizer sterilizes micro-organisms utilizing infrared heat produced by a ceramic core element. The ceramic element contains no asbestos and ensures maximum sterility without splatter across the work surface area. Complete sterilization occurs within 5-7sec at optimum sterilizing temperature of 1500°F (815.6°C). The small footprint makes the Bacti-Cinerator Sterilizer an ideal instrument for anaerobic and aerobic chambers alike. Several user friendly accessories are also available for the Bacti-Cinerator sterilizer

Specification

Model	FHM-3000A	FHM-3000C	FHM-3000D	FHM-3000E
Center High-temperature	825°C±50°C	825°C±50°C	825°C±50°C	825°C±50°C
Adjustable angle range	----	----	55°	55°
Max-Sterilizer Goods diameter	Φ14mm	Φ35mm	Φ14mm	Φ35mm
Length of Sterilizer	150mm	100mm	150mm	100mm
Dimensions (D x W x H) mm	185 x 98 x 185 mm	162 x 98 x 225 mm	159 x 100 x 260 mm	153 x 100 x 280 mm
Power	170W	320W	170W	320W
Weight	1.3kg	1.3kg	1.5kg	1.6kg



FHM-3000A




FHM-3000C



FHM-3000D



FHM-3000E



FHM-3000D and
FHM-3000E

Adjustable heater

Ordering information

No.	Code	Description
01	AS-07020-00	FHM-3000A , AC220V/AC120V, 50/60Hz, 1A
02	AS-07050-00	FHM-3000C , AC220V/AC120V, 50/60Hz, 1A
03	AS-07090-00	FHM-3000D , AC220V/AC120V, 50/60Hz, 1A
04	AS-07100-00	FHM-3000E , AC220V/AC120V, 50/60Hz, 1A
05	AS-07021-01	220V Heater for FHM-3000A
06	AS-07021-02	120V Heater for FHM-3000A
07	AS-07051-01	220V Heater for FHM-3000C
08	AS-07051-02	120V Heater for FHM-3000C
09	AS-07021-03	Holder for FHM-3000A
10	AS-07051-03	Holder for FHM-3000C